

xVision Totem

1.8 mm Series

XVA-1.8S-IN



Available for Rent or Purchase from Nationwide Video



Every detail of the Theatrixx Totem has been designed to ensure maximal impact and delivery of your message in a clear and appealing way. The Theatrixx Totem is a standalone, fully autonomous digital signage display. It can be used either as a free-standing structure (with optional locking casters) or as a digital power installed to a wall or suspended from the ceiling in any orientation. Its direct-view LED display ensures readability even in bright environments, and a strong plexiglass cover protects its surface against long term damage. Each Totem can be connected to WiFi and loaded with new content with

just a few clicks. A user-friendly PC application allows the management of your fleet of Totems on a local network, and creating new slides is as easy as designing a PowerPoint slide show. The software also provides detailed logging such as play counts, easily exportable to Excel. Totems can even be controlled from iOS or Android devices, and an optional, subscription-based cloud platform allows the handling of a larger fleet of device from anywhere in the world.

Features

- › **Multiple mounting options:** free-standing, wheeled, wall hanged and suspended.
- › **Built-in power supply:** single 120VAC inlet.
- › **Plug and Play operation:** user-friendly software gets you up and running in minutes.
- › **Built-in Wi-Fi** access point and client: easily connect to each device using your computer or smartphone.
- › **Fully autonomous professional digital signage player** built-in with scheduler.
- › **Auxiliary HDMI** input for external video sources.
- › **Daisy-chainable:** Connect up to 2 Totems together to create a perfectly synchronized display.
- › Integrated **remote monitoring, diagnostics and logging** of both the display and the player.

Ordering Information

XVA-1.8S-IN .. Theatrixx Totem - 1.8mm standalone LED Display - single width


XVA-2.5S-IN .. Theatrixx Totem - 2.5mm standalone LED Display - single width

XVA-FC-2S Theatrixx Totem - Dual flight case for 2 X single width totems - 24"W X 91"L X 34"H

XVA-MPA Theatrixx Totem - Multi-Purpose Adapter

XVA-WM Theatrixx Totem - Wall-Mount Bracket

Overview



Pixel		LED Control System	
Packaging	RGB SMD 3-in1	Max. Daisy Chain	Novastar Taurus Series (T50) 2 units
Pixel Pitch	1.80 mm	Physical Specifications	
Mechanical		Width	596 mm (23.46 in)
Module Resolution	160 x 120 px	Height	1,964 mm (77.32 in)
Module Dimensions	288 x 216 mm (11.34 x 8.5 in)	Depth	39 mm (1.53 in) - excl. control box and base
Panel Resolution	320 x 1,080 px	Weight	36 kg (79.4 lbs)
Installation	5 mounting points at the back, floor stand	Environmental Specifications	
Mounting points	4 x M8 threads in 550 x 550 mm pattern	Protection Rating	IP40
Cooling	Passive	Operating Temperature	- 10°C @ + 50°C
Optical		Storage Temperature	-40 °C @ +70 °C
Brightness	600 nits after calibration	Relative Humidity	10% to 95% non-condensing
Lifespan	50,000 hours	Power Requirements	
Color Temperature	2,500 - 6,500 K	Max Power Consumption	640 W/unit
Horizontal Viewing Angle	160°	Average Power Consumption	250 W/unit
Vertical Viewing Angle	160°	Input Voltage	100-240V, 50-60Hz auto-ranging
Processing		Certifications & Compliance	
Driving Mode	1/40	Electrical Safety	UL 60950-1:2007, CSA C22.2#60950-1:2007
Distribution Architecture	Common Anode	Electro Magnetic Compliance	FCC Part 15 Class A, ICES-003/NMB-003 Class A
Grayscale Depth	17 bits	Warranty	2 years
Refresh Rate	3,840 Hz		
Video Frame Rate	60 Hz		